


Newmev

GTN-PLUS



绿色 环保




Our innovative strippable blanket construction for highest contrast values and optimized quick release behaviour /

我们革新性的可剥离橡皮布结构可提供最佳的对
比度和最优的快速剥离性能

Newmev® GTN-PLUS

- ▶ Superior printing quality in terms of round dot shapes, good solid laydown and highest contrast values / 优秀的印刷质量，网点清晰锐利，实地平整，极高的对比度
- ▶ Optimized quick release behavior / 最佳的快速剥离性能
- ▶ Excellent resistance against edge marking, ideal for frequent changes of substrates and format sizes / 极佳的抗纸边切割效果，适合频繁更换大小版面尺寸

Product attributes / 产品属性	
Colour / 颜色	Green / 绿色
Identification / 标识	Product name & Made by Continental, batch-No. / 产品名称&大陆集团制造, 批次号
Thickness / 厚度	1.96 mm / 0.077"


Applications / 应用		
	Sheet-fed offset 单张纸-胶印	★★★★
	Packaging 包装	★★★
	UV printing UV印刷	
	Hybrid: conv. + UV 混合油墨: UV+普通油墨	★★★
	Waterbased varnishes 水性上光	
	UV varnishes UV上光	
	Newspaper printing 报纸印刷	
	Heatset printing 热固印刷	
	Label printing 标签印刷	
	Business form 商业表格	

★★★★ Excellent / 优 ★★★ Good / 良好 ★ Suitable / 适宜

Optimized surface for high-quality half tone and solid print / 最佳优化的面层用于高质量半色调印刷品和专色印刷印刷品和专色印刷

Strippable construction (above second fabric layer) / 可剥离结构 (在第二结构层以上)

Double compressible layer construction supports minimizing press shock streak / 双层可压缩气垫层结构减少机器冲击杠



Technical specification / 技术参数	
Compressibility at / 可压缩率 1,350 kPa	approx. 12% 大约12%
Hardness total / 整体硬度	approx. 78 Shore A / 大约邵氏78°A
Surface rubber / 表面橡胶硬度	approx. 48 Shore A 大约邵氏48°A
Roughness R _z / 粗糙度R _z	6.8 µm (fineground) 6.8 µm (精磨)